

# BRAKE FLUID

03/07/2016  
5015

Brake fluid, intended for hydraulic brake systems. Its composition provides a high chemical stability, excellent resistance against residue formation, very good stability towards oxidation and is compatible with all materials present in the circuit.

## APPLICATIONS

It is suitable for all hydraulic brake circuits where the manufacturer recommends a fluid, which meets the specifications mentioned below. It is also suitable for numerous steering and clutch systems and can be used from -40°C till 260°C.

## FEATURES

Boiling Point : high boiling point, safe braking.  
Anti-corrosion properties : complete brake system protection.  
Elastomer compatibility: no leakage or fluid losses.

## SPECIFICATION LEVEL

FMVSS	116 DOT 4	SAE	J 1703
FMVSS	116 DOT3	SAE	J 1704
ISO	4925 Class 3&4		

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	2.1
pH	ASTM D1287		8.5
Equilibrium Reflux Boiling Point (ERBP)	ASTM D1120	°C	263
Wet Equilibrium Reflux Boiling Point (WERBP)	ASTM D1120	°C	165
Density at 20°C	ASTM D4052	g/ml	1.040
Kinematic viscosity at -40°C	ASTM D445	mm <sup>2</sup> /s	1400

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolflubes.com](http://www.wolflubes.com)

